


M575-595N72LB-BF-F7

144CELLS HALF-CUT
Bifacial N-TOPCon PV Module
Black Frame



25 YEARS Product guarantee

30 YEARS Output guarantee

575-595Wp Power range

23,03% Maximum efficiency

0,40% Yearly degradation

SMBB Excellent Cell Efficiency
Super multi Bus Bar technology increases the efficiency of the modules

PID Resistance to power degradation
Resistance to power degradation caused by Potential-Induced Degradation PID effect, thanks to strict quality control in the module production process and other subassemblies

Weak Illumination Better Weak Illumination Response
More power output in weak light conditions, such as haze, clouds and early morning

Adapted to harsh outdoor environments
Resistant to harsh environments such as salt, ammonia, sand, high temperatures and high humidity environments


Highest production standards
Guarantees of operational reliability and quality module implementations go far beyond requirements specified in certificates




IEC 61215: Design suitability and type approval
IEC 61730: Safety qualification
IEC 61701: Salt mist corrosion testing
IEC 62716: Ammonia corrosion testing
IEC 60068: Environmental testing: Dust and sand

With subsidiaries in more than 50 countries and business activities in over 150 countries, LEDVANCE is committed to supplying reliable and durable PV products to customers to create together a greener planet.


Dimensions of PV module (mm)



Current-voltage curve of the module by different insolation



Current-voltage curve of the PV module by temperature



ELECTRICAL CHARACTERISTIC | STC ¹⁾

Power Level	575	580	585	590	595
Nominal power Watt P_{max} (Wp)	575	580	585	590	595
Maximum power voltage V_{mp} (V)	42.44	42.59	42.77	42.92	43.06
Maximum power current I_{mp} (A)	13.55	13.62	13.68	13.75	13.82
Open circuit voltage V_{oc} (V)	51.28	51.48	51.68	51.88	52.08
Short circuit current I_{sc} (A)	14.30	14.36	14.42	14.48	14.54
Module efficiency η (%)	22.26	22.45	22.65	22.84	23.03

Measuring tolerance: $\pm 3\%$

Bifacial Output-Backside Power Gain | 575w ²⁾

Power gain	5%	10%	15%	20%	25%
Maximum power P_{max} (Wp)	604	633	662	690	719
Maximum power voltage V_{mp} (V)	42.82	42.82	42.82	42.83	42.83
Open circuit voltage V_{oc} (V)	51.20	51.20	51.20	51.30	51.30
Short circuit current I_{sc} (A)	14.74	15.30	15.84	16.41	16.97
Maximum power current I_{mp} (A)	14.11	14.78	15.46	16.12	16.79

ELECTRICAL CHARACTERISTIC | NMOT ²⁾

Power Level	575	580	585	590	595
Maximum power P_{max} (Wp)	433	437	441	445	449
Maximum power voltage V_{mp} (V)	39.73	39.84	39.95	40.06	40.17
Maximum power current I_{mp} (A)	10.90	10.97	11.04	11.11	11.18
Open circuit voltage V_{oc} (V)	48.70	48.89	49.08	49.27	49.46
Short circuit current I_{sc} (A)	11.55	11.59	11.64	11.69	11.74

Measuring tolerance: $\pm 3\%$

WORKING CONDITIONS

Maximum system voltage	1500 V DC
Operating temperature	-40°C~+85°C
Operating humidity	5~85%
Maximum series fuse	30 A
Front/Rear Load	5400/2400Pa

MECHANICAL DATA

Solar cells	N-TOPCon
Number of cells	144 (6x24) pcs
Size of cells	182 x 91 mm
Module dimension	2278 x 1134 x 30 mm
Frame color	BF - Black
Weight	31.2 kg
Glass	Front Glass, 2.0mmAR coated semi-tempered glass Black Glass, 2.0mm glazed semi-tempered glass
Type of frame	Anodized aluminum alloy
Junction box	IP68, 3 diodes
Cables	4 mm ² , Portrait: 300 mm or 1400mm
Connectors	MC4-EVO2

TEMPERATURE RATINGS

NMOT	45 \pm 2 °C
Temperature coefficient of P_{max}	-0.290% / °C
Temperature coefficient of V_{oc}	-0.260% / °C
Temperature coefficient of I_{sc}	0.045% / °C

PACKAGING CONFIGURATION

Piece / Box	36
Size of packing	2320 x 1130 x 1270 mm
Weight of packing	1178 kg
Piece / Container (40'HC)	720

FOOTNOTES:

- 1) STC (Standard Test Conditions): 1000W/m² solar irradiance, cell temperature 25°C, AM 1.5G
- 2) NMOT (nominal cell operating temperature): insolation 800W/m², ambient temperature 20°C, AM 1.5G, wind speed 1m/s

CAUTION:

- Do not connect two or more strings of modules to one fuse.
- The electrical data in this product sheet does not refer to a single module and is not part of the offer, it is used to compare different types of modules only.
- Due to continuous technical innovation, development and product improvement, technical data contained in this product sheet is subject to change at any time without notice and may not be the basis for any damage claims.